

CP系列

便携式储能电源



- 1

小巧美观，即提即用
- 2

随应用场景选择充电方式，在家标配市充，户外出行车充/太阳能板
- 3

兼容强满足多设备充电需求
- 4

理想正弦波交流电稳定无损害
- 5

多重保护及告警系统，安全可靠

型 号	CP330-E	CP500-E	CP1000-E	CP2000-E
额定功率	330W	500W	1000W	2200W
额定电量	288.6Wh	519Wh	799.2Wh	2150Wh
额定容量	3.7V/78000mAh	3.7V/140400mAh	3.7V/216000mAh	3.2V/672000mAh
过载保护	360±20W	550±40W	1100±80W	2200±100W
交流输出	110V±10%/60HZ	110V±10%/60HZ	110V±10%/60HZ	110V/60HZ或220V/50HZ
输出波形	纯正弦波	纯正弦波	纯正弦波	纯正弦波
USB 输出	QC3.0/18W	QC3.0/18W	QC3.0/18W	QC3.0/18W
Type-C 输出	PD60W	PD60W	PD60W	PD60W
DC55*2.5 点烟口输出	12V/10A	14V/8A	14V/8A	14V/8A
无线充	5W	10W	10W	支持，自由匹配电池组
充电输入电压	12-24V	12-26V	12-26V	市电（100-240V）直接对产品充电
工作使用温度	-10-40℃	-10-40℃	-10-40℃	-10-40℃
重量（净重）	≈ 3.3kg	≈ 6.8kg	≈7.5kg	≈31kg
产品尺寸（长*宽*高）	205*155*165mm	290*194*200mm	290*194*200mm	460*366*260mm
AC输出支持	美/日规、澳规、欧规、中规等			



深圳昆宇电源科技有限公司
网址:WWW.COSPOWERS.COM
地址:深圳市宝安区燕罗街道罗田社区第三工业区广田路2号
电话:0755-33185898
版权及最终解释权归深圳昆宇电源科技有限公司所有

CP SERIES

COSPOWERS

PORTABLE ENERGY STORAGE POWER SUPPLY



- 1 Small and beautiful, ready to use
- 2 Choose the charging mode according to the application scenario, standard mains charging at home, and Outdoor vehicle charging/solar panels
- 3 Strong compatibility to meet the charge needs of multiple devices
- 4 Ideal sine wave AC is stable without damage
- 5 Multiple protection and alarm systems, safe and reliable

Model	CP330-E	CP500-E	CP1000-E	CP2000-E
Rated power	330W	500W	1000W	2200W
Rated energy	288.6Wh	519Wh	799.2Wh	2150Wh
Standard capacity	3.7V/78000mAh	3.7V/140400mAh	3.7V/216000mAh	3.2V/672000mAh
Overload protection	360±20W	550±40W	1100±80W	2200±100W
AC output	110V±10%/60HZ	110V±10%/60HZ	110V±10%/60HZ	110V/60HZ pr 220V/50HZ
Output wave form	Pure sine wave	Pure sine wave	Pure sine wave	Pure sine wave
USB Output	QC3.0/18W	QC3.0/18W	QC3.0/18W	QC3.0/18W
Type-C Output	PD60W	PD60W	PD60W	PD60W
DC55*2.5 cigarette lighting port output	12V/10A	14V/8A	14V/8A	14V/8A
Wireless charge	5W	10W	10W	Supporting, free matching of battery pack
Charge input voltage	12-24V	12-26V	12-26V	Mains power (100-240V) directly charges the product
Operating temperature	-10-40°C	-10-40°C	-10-40°C	-10-40°C
Weight(net weight)	≈ 3.3kg	≈ 6.8kg	≈7.5kg	≈31kg
Size	205*155*165mm	290*194*200mm	290*194*200mm	460*366*260mm
AC output support	US/JA, EUROPE, AU, CN			



Shenzhen Coslight Power Technology Co., Ltd.

W: WWW.COSPOWERS.COM

A: No.2, Guangtian Road, No.3 Industrial Zone, Luotian Community, Yanluo Street, Baoan District, Shenzhen, Guangdong Province, P.R.C

T: +86-755-33185898

Copyright and final interpretation rights belong to Shenzhen Coslight Power Technology Co., Ltd.